

acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

SECTION 1: Identification

1.1 Product identifier

Trade name Cerakote MC-157: Matte Ceramic Clear

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

General use

1.3 Details of the supplier of the safety data sheet

NIC Industries, Inc 7050 6th St. White City Oregon 97503 United States

Telephone: 866-774-7628 e-mail: sds@nicindustries.com Website: www.nicindustries.com

1.4 Emergency telephone number

Emergency information service

1-800-633-8253 (USA & Canada)

The information contained in this Safety Data Sheet (SDS) is, to the best of our knowledge, true and accurate and presented in good faith. NIC Industries, Inc. makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. Because many factors may affect processing or application/use of this product, this data is offered solely for the user's consideration, investigation and verification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or process. Regulatory requirements are subject to change and may differ from one location to another. It is the responsibility of the buyer/user to ensure its activities comply with all local, state and federal regulations.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
A.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
A.2	Skin corrosion/irritation	1B	Skin Corr. 1B	H314
A.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.4S	Skin sensitization		Skin Sens. 1	H317
B.6	Flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word

DANGER

- Pictograms

GHS02, GHS05, GHS07







- Hazard statements

H226 Flammable liquid and vapor. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

- Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dusts or mists.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/eye protection/face protection. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

Ambient Cure Refractory Resin, p-chlorobenzotrifluoride

2.3 Other hazards

Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%
p-chlorobenzotrifluoride	CAS No 98-56-6	50 – < 75
Ambient Cure Refractory Resin	CAS No Trade Secret	25 – < 50
Flow Agent	CAS No Trade Secret	<1

^{**} Trade Secret: In accordance with OSHA Hazard Communication Standard 29 CFR 1910.1200(i) and in accordance with the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS), the specific identity and/or exact percentage (concentration) of the composition has been withheld as a "Trade Secret."

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

None.



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Dry extinguishing powder, BC-powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder.

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

This information is not available.

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/ impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid
Color	Clear
Particle	Not relevant (liquid)
Odor	Ammoniacal

Other safety parameters

pH (value)	Not determined
Melting point/freezing point	Not determined
Initial boiling point and boiling range	>133.8 °C
Flash point	39 °C
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant (fluid)
Vapor pressure	0.018 Pa at 25 °C
Density	Not determined
Vapor density	Not available
Relative density	Not available



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

Solubility(ies)	Not determined
Partition coefficient	
- n-octanol/water (log KOW)	Not available
Auto-ignition temperature	600 °C
Viscosity	Not determined
Explosive properties	None
Oxidizing properties	None

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T1 (maximum permissible surface temperature on the equipment:
	450°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers. Alkalines. Strong acids.

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, and silicon oxides may be produced from all coating formulations. Chlorine-containing gases, fluorine-containing gases may be produced in products containing p-chlorobenzotrifluoride. Hazardous combustion products: see section 5.



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed.

- Acute toxicity estimate (ATE)

Oral

Acute toxicity estimate (ATE) of components of the mixture

742.6 ^{mg}/_{kg}

Name of substance	CAS No	Exposure route	ATE
Ambient Cure Refractory Resin	Trade Secret	Oral	>300 ^{mg} / _{kg}
Flow Agent	Trade Secret	Inhalation: vapor	11 ^{mg} / _l /4h
Flow Agent	Trade Secret	Inhalation: dust/mist	>1.9 ^{mg} / _I /4h

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
p-chlorobenzotrifluoride	98-56-6	2B	

Legend

2B Possibly carcinogenic to humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
p-chlorobenzotrifluoride	98-56-6	LC50	6.5 ^{mg} / _l	Fish	24 h
p-chlorobenzotrifluoride	98-56-6	ErC50	>0.41 ^{mg} / _l	Algae	72 h
p-chlorobenzotrifluoride	98-56-6	EC50	>0.41 ^{mg} / _l	Algae	72 h
Ambient Cure Refractory Resin	Trade Secret	LC50	57.1 ^{mg} / _l	Zebra fish	96 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
p-chlorobenzotrifluoride	98-56-6	EC50	242.1 ^{mg} / _l	Microorganisms	30 min

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

SECTION 13: Disposal considerations

Waste treatment methods

Product/packaging disposal

Do not empty into drains. Avoid release to the environment. Contact a licensed professional waste disposal service to dispose of this material and its packaging.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Hazardous waste code(s)

The waste code(s) should be assigned in discussion between the user and the waste disposal company.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

1	4.	1	u	ľ	V	n	u	n	1	b	e	r

DOT UN 1263 IMDG-Code UN 1263 ICAO-TI UN 1263

14.2 UN proper shipping name

DOT Paint related material IMDG-Code PAINT RELATED MATERIAL ICAO-TI Paint related material

Transport hazard class(es) 14.3

DOT 3 3 IMDG-Code ICAO-TI 3

14.4 Packing group

DOT Ш IMDG-Code Ш ICAO-TI Ш

14.5 **Environmental hazards**

Environmentally hazardous substance (aquatic environment)

hazardous to the aquatic environment

p-chlorobenzotrifluoride

14.6 Special precautions for user

There is no additional information.



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1263, Paint related material, 3, III, environment-

ally hazardous

Danger label(s) 3, fish and tree





Environmental hazards yes (hazardous to the aquatic environment)

Special provisions (SP) 367, B1, B52, B131, IB3, T2, TP1, TP29

ERG No 128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant Yes (hazardous to the aquatic environment)

Danger label(s) 3, fish and tree





Special provisions (SP) 163, 223, 367, 955

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
EmS F-E, <u>S-E</u>
Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



Special provisions (SP) A3, A72, A192

Excepted quantities (EQ) E1
Limited quantities (LQ) 10 L



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

All ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed.

- Specific Toxic Chemical Listings (EPCRA Section 313) None of the ingredients are listed.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) None of the ingredients are listed.

Clean Air Act

None of the ingredients are listed.

Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA) None of the ingredients are listed.
- Hazardous Substances List (MN-ERTK)
 None of the ingredients are listed.
- Hazardous Substance List (NJ-RTK) None of the ingredients are listed.
- Hazardous Substance List (Chapter 323) (PA-RTK) None of the ingredients are listed.
- Hazardous Substance List (RI-RTK)
 None of the ingredients are listed.

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name of substance	CAS No	Remarks	Type of the toxicity
n-chlorobenzotrifluoride	98-56-6		cancer

VOC content

All Cerakote coatings are VOC compliant under the EPA and have low to no VOC content. To find out the VOC content of an individual coating please contact sds@nicindustries.com for more information.



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

Industry or sector specific available guidance(s)

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of haz- ard	Description
Flammability	2	Material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	3	Material that, under emergency conditions, can cause serious or permanent injury
Instability	0	Material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	Not all ingredients are listed
CA	DSL	Not all ingredients are listed
CA	NDSL	Not all ingredients are listed
CN	IECSC	Not all ingredients are listed
EU	ECSI	Not all ingredients are listed
EU	REACH Reg.	Not all ingredients are listed
JP	CSCL-ENCS	Not all ingredients are listed
JP	ISHA-ENCS	Not all ingredients are listed
KR	KECI	All ingredients are listed
NZ	NZIoC	All ingredients are listed
PH	PICCS	Not all ingredients are listed
TW	TCSI	All ingredients are listed
US	TSCA	All ingredients are listed

Legend

Australian Inventory of Industrial Chemicals List of Existing and New Chemical Substances (CSCL-ENCS) CSCL-ENCS

DSL

ECSI

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
Inventory of Existing and New Chemical Substances (ISHA-ENCS) **IECSC**

ISHA-ENCS

KECI Korea Existing Chemicals Inventory Non-domestic Substances List (NDSL) **NDSL** NZIoC

New Zealand Inventory of Chemicals Philippine Inventory of Chemicals and Chemical Substances (PICCS) **PICCS**

REACH Reg. REACH registered substances TCSI

Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % leth- ality during a specified time interval
NLP	No-Longer Polymer
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative



acc. to 29 CFR 1910.1200 App D

Cerakote MC-157: Matte Ceramic Clear

Version number: 2.0 Revision: 06/22/2022

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.