

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## SECTION 1: Identification

### 1.1 Product identifier

Trade name **Cerakote MC-161: Matte Ceramic Clear**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses **General use**

### 1.3 Details of the supplier of the safety data sheet

NIC Industries, Inc  
7050 6th St.  
White City Oregon 97503  
United States

Telephone: 866-774-7628  
e-mail: sds@nicindustries.com  
Website: www.nicindustries.com

### 1.4 Emergency telephone number

Emergency information service **1-800-633-8253 (USA & Canada)**

The information contained in this Safety Data Sheet (SDS) is, to the best of our knowledge, true and accurate and presented in good faith. NIC Industries, Inc. makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. Because many factors may affect processing or application/use of this product, this data is offered solely for the user's consideration, investigation and verification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or process. Regulatory requirements are subject to change and may differ from one location to another. It is the responsibility of the buyer/user to ensure its activities comply with all local, state and federal regulations.

## SECTION 2: Hazard(s) identification

### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Hazard class and category code(s)

Classification acc. to GHS				
Section	Hazard class	Category	Hazard class and category	Hazard statement
A.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
A.2	Skin corrosion/irritation	1B	Skin Corr. 1B	H314
A.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.4S	Skin sensitization	1	Skin Sens. 1	H317
B.6	Flammable liquid	2	Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16.

### The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word **DANGER**

- Pictograms

GHS02, GHS05, GHS07



- Hazard statements

- H225 Highly flammable liquid and vapor.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.

- Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dusts or mists.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/eye protection/face protection.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P302+P352 If on skin: Wash with plenty of water.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a poison center/doctor.
- P321 Specific treatment (see on this label).
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling **Ambient Cure Refractory Resin, Curative**

## 2.3 Other hazards

Hazards not otherwise classified

- May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).
- Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%
Tert-butyl acetate	CAS No 540-88-5	50 - < 75
Ambient Cure Refractory Resin	CAS No Trade Secret	10 - < 25
Curative	CAS No Trade Secret	5 - < 10
Rheology Modifier	CAS No Trade Secret	1 - < 5

\*\* Trade Secret: In accordance with OSHA Hazard Communication Standard 29 CFR 1910.1200(i) and in accordance with the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS), the specific identity and/or exact percentage (concentration) of the composition has been withheld as a "Trade Secret"

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

None.

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, Dry extinguishing powder, BC-powder, Carbon dioxide (CO<sub>2</sub>)

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder.

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	tert-butyl acetate	540-88-5	PEL (CA)	200	950						Cal/ OSHA PEL
US	tert-butyl acetate	540-88-5	REL	200 (10 h)	950 (10 h)						NIOSH REL

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	tert-butyl acetate	540-88-5	TLV®	50		150					ACGIH® 2022
US	tert-butyl acetate	540-88-5	PEL	200	950						29 CFR 1910.1000

**Notation**

Ceiling-C  
STEL

ceiling value is a limit value above which exposure should not occur  
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

##### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

Physical state	Liquid
Color	Clear
Particle	Not relevant (liquid)
Particle size	Not available
Odor	Characteristic

**Other safety parameters**

pH (value)	Not determined
Melting point/freezing point	Not determined
Initial boiling point and boiling range	97.8 °C
Flash point	19 °C
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant (fluid)
Explosive limits	Not determined
Vapor pressure	42 Torr at 20 °C
Density	Not determined
Vapor density	Not available
Relative density	Not available
Solubility(ies)	Not determined

Partition coefficient

- n-octanol/water (log KOW)	Not available
-----------------------------	---------------

Auto-ignition temperature	270 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	Not relevant

Viscosity Not determined

- Kinematic viscosity	Not determined
-----------------------	----------------

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

Explosive properties	None
Oxidizing properties	None

There is no additional information

## 9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2B (maximum permissible surface temperature on the equipment: 260°C)
--	---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition. Reacts with water.

If heated:

Risk of ignition.

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.5 Incompatible materials

Oxidizers. Acids. Strong bases.

### 10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, and silicon oxides may be produced from all coating formulations. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4: May be harmful in contact with skin.



# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

- Acute toxicity estimate (ATE)  
Oral 1,387 mg/kg

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Ambient Cure Refractory Resin	Trade Secret	Oral	>300 mg/kg
Curative	Trade Secret	Oral	500 mg/kg
Rheology Modifier	Trade Secret	Dermal	>1,000 mg/kg

**Skin corrosion/irritation**

Causes severe skin burns and eye damage.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitization**

May cause an allergic skin reaction.

**Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

**Carcinogenicity**

Shall not be classified as carcinogenic.

**Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

**Specific target organ toxicity - single exposure**

Shall not be classified as a specific target organ toxicant (single exposure).

**Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

**Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Tert-butyl acetate	540-88-5	LC50	240 mg/l	Fish	96 h
Tert-butyl acetate	540-88-5	EC50	410 mg/l	Aquatic invertebrates	24 h
Tert-butyl acetate	540-88-5	ErC50	64 mg/l	Algae	96 h

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Ambient Cure Refractory Resin	Trade Secret	LC50	57.1 mg/l	Zebra fish	96 h
Curative	Trade Secret	LC50	>934 mg/l	Fish	96 h
Curative	Trade Secret	EC50	331 mg/l	Aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Curative	Trade Secret	EC50	43 mg/l	Microorganisms	5.75 h

**12.2 Persistence and degradability**

Data are not available.

**12.3 Bioaccumulative potential**

Data are not available.

**12.4 Mobility in soil**

Data are not available.

**12.5 Results of PBT and vPvB assessment**

Data are not available.

**12.6 Endocrine disrupting properties**

None of the ingredients are listed.

**12.7 Other adverse effects**

Data are not available.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Product/packaging disposal

Do not empty into drains. Avoid release to the environment. Contact a licensed professional waste disposal service to dispose of this material and its packaging.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Hazardous waste code(s)

The waste code(s) should be assigned in discussion between the user and the waste disposal company.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## SECTION 14: Transport information

**14.1 UN number**

DOT	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263

**14.2 UN proper shipping name**

DOT	Paint related material
IMDG-Code	PAINT RELATED MATERIAL
ICAO-TI	Paint related material

**14.3 Transport hazard class(es)**

DOT	3
IMDG-Code	3
ICAO-TI	3

**14.4 Packing group**

DOT	II
IMDG-Code	II
ICAO-TI	II

**14.5 Environmental hazards**

non-environmentally hazardous acc. to the dangerous goods regulations

**14.6 Special precautions for user**

There is no additional information.

**14.7 Transport in bulk according to IMO instruments**

The cargo is not intended to be carried in bulk.

**Information for each of the UN Model Regulations**

**Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

Particulars in the shipper's declaration	UN1263, Paint related material, 3, II
Reportable quantity (RQ)	6,998 lbs (3,177 kg) (Tert-butyl acetate)
Danger label(s)	3



Special provisions (SP)	149, 367, B52, B131, IB2, T4, TP1, TP8, TP28
ERG No	128

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant -  
 Danger label(s) 3



Special provisions (SP) 163, 367  
 Excepted quantities (EQ) E2  
 Limited quantities (LQ) 5 L  
 EmS F-E, S-E  
 Stowage category B

## International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3, A72, A192  
 Excepted quantities (EQ) E2  
 Limited quantities (LQ) 1 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

**Toxic Substance Control Act (TSCA)** All ingredients are listed

#### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed.

- Specific Toxic Chemical Listings (EPCRA Section 313)

None of the ingredients are listed.

#### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
Tert-butyl acetate	540-88-5		1	5000 (2270)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

#### Clean Air Act

None of the ingredients are listed.

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## Right to Know Hazardous Substance List

### - Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Tert-butyl acetate	540-88-5				1.0 %

### - Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Tert-butyl acetate	540-88-5	A, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Tert-butyl acetate	540-88-5		F3

Legend

- F3 Flammable - Third Degree

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	CAS No	Classification
Tert-butyl acetate	540-88-5	E

Legend

- E Environmental hazard

### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Tert-butyl acetate	540-88-5	T

Legend

- T Toxicity (ACGIH®)

## California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

None of the ingredients are listed.

## VOC content

All Cerakote coatings are VOC compliant under the EPA and have low to no VOC content. To find out the VOC content of an individual coating please contact [sds@nicindustries.com](mailto:sds@nicindustries.com) for more information.

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

## Industry or sector specific available guidance(s)

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	Material that can be ignited under almost all ambient temperature conditions
Health	3	Material that, under emergency conditions, can cause serious or permanent injury
Instability	0	Material that is normally stable, even under fire conditions
Special hazard		

## National inventories

Country	Inventory	Status
AU	AIIC	Not all ingredients are listed
CA	DSL	Not all ingredients are listed
CA	NDSL	Not all ingredients are listed
CN	IECSC	Not all ingredients are listed
EU	ECSI	Not all ingredients are listed
EU	REACH Reg.	Not all ingredients are listed
JP	CSCL-ENCS	Not all ingredients are listed
JP	ISHA-ENCS	Not all ingredients are listed
KR	KECI	All ingredients are listed
MX	INSQ	Not all ingredients are listed
NZ	NZIoC	All ingredients are listed
PH	PICCS	Not all ingredients are listed
TR	CICR	Not all ingredients are listed
TW	TCSI	All ingredients are listed
US	TSCA	All ingredients are listed

### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

Legend

REACH Reg. REACH registered substances  
 TCSI Taiwan Chemical Substance Inventory  
 TSCA Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2022	From ACGIH®, 2022 TLVs® and BEIs® Book. Copyright 2022. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: <a href="http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement">http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement</a>
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization

# Cerakote MC-161: Matte Ceramic Clear

Version number: 2.2

Revision: 01/03/2023

Abbr.	Descriptions of used abbreviations
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

## Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

## Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

## List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.